

Transformer Accessories

www.otaner.com

Air Breather

Contact us: E-mail robert@otaner.com
phone 1 (519) 760-6040

Rev 7- 2018/10/10

Issued by: Roberto L. Caldart

Manufacturer: Comem, Italy

Silicagel: environmentally friendly orange silicon oxide that turns green when moist.

Structure material

Cylinder: polycarbonate UV-ray and saline environment resistant

Cylinder protection tube: stainless steel(except 4MB)

Fasteners: Stainless steel

Flange or threaded piece: cast aluminum

Oil bath: Polycarbonate

Transport caps: plastic

Surface protection: Aluminum parts are painted with double coat of polyurethane light gray (40µm or 1.6mils). Stainless steel parts are not painted.

Operating temperature range:

-40°F to +212°F (-40°C to +100°C)

Notes:

1) For further information see our brochure and web site.

2) Other options and technical data are available upon request



Model DB



Model DA

Model		Silicagel Weight			OD	Height	Flange ID/OD or Thread	
2DA	Top: flange; Bottom: oil bath	1.7 lbs 0.76 Kg			5.5" 140mm	10.4" 265mm	1.2"/3.9" 30/100mm	
2DB	Top: threaded; Bottom: oil bath	1.7 lbs 0.76 Kg			5.5" 140mm	8.25" 210mm	1"	
3DB	Top: threaded; Bottom: oil bath	4.8 lbs 2.2 Kg			6.9" 175mm	12.2" 310mm	1 1/2"	
4MB	Top and Bottom: threaded	6.8 lbs 3.1 Kg			6.9" 175mm	15.7" 400mm	1 1/2"	
4DB	Top: threaded; Bottom: oil bath	11.5 lbs 5.2 Kg			6.9" 175mm	22.0" 560mm	1 1/2"	
4DA	Top: flange; Bottom: oil bath	11.5 lbs 5.2 Kg			6.9" 175mm	24.0" 610mm	1.7"/5.1" 44/130mm	
5DA	Top: flange; Bottom: oil bath	23 lbs 10.5Kg			8.7" 220mm	26.6" 675mm	2.2"/5.5" 57/140mm	
6DA	Top: flange; Bottom: oil bath	33.5 lbs 15.2Kg			8.7" 220mm	35.2" 895mm	2.2"/5.5" 57/140mm	
7DA	Top: flange; Bottom: oil bath	56 lbs 25.6Kg			13.0" 330mm	33.0" 840mm	4.3"/5.5" 110/140mm	
-	Silica gel in buckets	22.0 lbs 10.0 Kg			-	-	-	
							Page 1 of 1	