

www.otaner.com

## Pressure Relief Device

**Contact us:** E-mail [robert@otaner.com](mailto:robert@otaner.com);  
phone 1 (519) 760-6040

Doc ref: PRD

Rev 4 - 2018/02/02

Issued by: Roberto L. Caldart

**Manufacturer:** Comem, Italy

**Application:** for transformer with expansion tank and filled with oil, and tanks with gas cushion.

## Material

Shroud: plastic UV-ray resistant

Valve: aluminum

Gaskets: NBR

Fasteners: Stainless steel

**Contacts:**

## Change-over micro switch

Breaking capacity: 6A, 125/250VAC

Terminal box with outlet thread PG13.5

Insulation class: 2kVAC/1min, 50/60Hz

Notes:

1) Indicated oil volumes are a suggestion only. Multiple valves can be used for larger volumes, if necessary.

**Surface protection:** Aluminum parts are painted with double coat of polyurethane light gray (40µm or 1.6mil). Plastic parts are not painted.

**Operating temperature range:**

-40°F to +248°F (-40°C to +120°C)

For further information see our brochure.



## With Shroud

### Without Shroud

Model	Application 1)	Operating Pressure	Stock	Contact	Shroud	Weight	OD	Flange ID/OD
50T	800 US Gallons 3,000 liters	8psi / 56kPa	NO	One	YES	4.6 lbs 2.1 Kg	6.9” 175mm	3.1”/6.5” 80/165mm
80T	2,400 US Gallons 9,000 liters	3 to 13psi / 20 to 90kPa	NO	0 to 3	YES/NO	8.4 lbs 3.8 Kg	8.3” 210mm	4.25”/7.9” 108/200mm
125T	6,600 US Gallons 25,000 liters	10psi / 70kPa	NO	One	YES	17 lbs 7.5 Kg	11.3” 288mm	6.1”/10.9” 155/278mm
								Page 1 of 1